Printing date 21.01.2021 Version number 106 Revision: 05.01.2021

SECTION 1: Identification of the substance/mixture and of the company undertaking

- 1.1 Product identifier
- Trade name LPZ/II
- **UFI:** 0020-T0PQ-Ū00F-1VQ8
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture

Industrial use.

Restrictions on use apply to this product according to Regulation (EU) no. 1907/2006 Annex XVII (see section 15)

- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Riepe GmbH & Co. KG

Theodor Rosenbaum Str. 28-30

32257 Bünde - Deutschland

Tel.: +49 (0) 5223 - 687407-0

Fax: +49 (0) 5223 - 687407-50

E-Mail: info@riepe.eu

- Informing department:

Tel.: +49 (0) 5223 - 687407-0

E-mail: info@riepe.eu

- 1.4 Emergency telephone number:

Poison Control Center, Mainz Tel. 00 49 / 61 31 / 19 240

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms





GHS02 GHS07

- Signal word Danger
- Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 21.01.2021 Version number 106 Revision: 05.01.2021

Trade name LPZ/II

(Contd. of page 1)

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Mixture of the substances listed below with harmless additions

- Dangerous components:						
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol	Flam. Liq. 2, H225; Eye Irrit. 2, H319 90 - 9	9%			

- Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General advice: Instantly remove any clothing soiled by the product.
- After inhalation Supply fresh air; consult doctor in case of symptoms.
- After skin contact

Remove contaminated clothing immediately. Wash affected areas with plenty of water und soap. If irritation continues, contact a doctor.

- After eye contact

Rinse immediately opened eye for several minutes under running water. Then consult doctor.

- After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting: instantly call for medical help.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures. In case of incomplete combustion carbon monoxide can arise. Fumes are heavier than air and distributed over ground. Inflammation is possible from a far distance.

- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained breathing apparatus.

See section 8.

(Contd. on page 3)

Printing date 21.01.2021 Version number 106 Revision: 05.01.2021

Trade name LPZ/II

(Contd. of page 2)

- Additional information

Endangered containers in the surrounding area should be cooled with a water-hose.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment and keep unprotected persons away.

Extinguish naked flames. Remove flammable sources. No smoking. Avoid sparks. Avoid contact with skin, eyes and clothing. Avoid inhalation of fumes. Air contaminated rooms thoroughly. Protect against electrostatic sparks.

- 6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

Dilute with much water.

If large amounts are released, the authorities must be informed.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Contaminated material has to be disposed as waste (see item 13).

- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with eyes or skin.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage

Protect against direct sunlight, other sources of heat and ignition.

Store in cool, dry conditions in well sealed containers.

- Requirements to be met by storerooms and containers:

Observe official regulations on storage and handling of water harzardous substances

- Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions:

Pay attention to regulations/technical rules for the storage of combustible liquids.

- Storage class 3 (VCI Konzept, 2007)
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Additional information about design of technical systems:

Room ventilation i.e. vacuum suction. Measures to be taken against electro-static sparks.

(Contd. on page 4)

Printing date 21.01.2021 Version number 106 Revision: 05.01.2021

Trade name LPZ/II

(Contd. of page 3)

- Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- DNELs					
64-17-5 et	64-17-5 ethanol				
Oral	DNEL (population)	87 mg/kg bw/day (Long-term, systemic effects)			
Dermal	DNEL (worker)	343 mg/kg bw/day (Long-term, systemic effects)			
	DNEL (population)	206 mg/kg bw/day (Long-term, systemic effects)			
Inhalative	DNEL (worker)	1,900 mg/m³ (Acute, local effects)			
		950 mg/m³ (Long-term, systemic effects)			
	DNEL (population)	950 mg/m³ (Acute, local effects)			
		114 mg/m³ (Long-term, systemic effects)			
- PNECs					
64-17-5 et	64-17-5 ethanol				

- PNECs			
64-17-5 ethanol			
PNEC water	r 2.75 mg/l (intermittent releases)		
	0.96 mg/l (freshwater)		
	0.79 mg/l (marine water)		
PNEC sediment 3.6 mg/kg dw (freshwater)			
	2.9 mg/kg dw (marine water)		
PNEC soil	0.63 mg/kg dw (soil)		
PNEC STP	580 mg/l (sewage plant)		

- Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- Personal protective equipment
- General protective and hygienic measures

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Gases, fumes and aerosols should not be inhaled.

- Breathing equipment:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

- Recommended filter device for short term use: Combination filter A-P2
- Protection of hands: Solvent resistant gloves
- Material of gloves

Butylrubber, BR, recommended thickness of the material: ≥ 0.7 mm, penetration time: ≥ 480 min.

Fluorocarbon rubber (Viton), recommended thickness of the material: ≥ 0.7 mm, penetration time: ≥ 480 min.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

Change gloves if notice sign of disenchantment.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Tightly sealed safety glasses.

(Contd. on page 5)

Printing date 21.01.2021 Version number 106 Revision: 05.01.2021

Trade name LPZ/II

(Contd. of page 4)

- Body protection:

Standard proctective clothing. Chemical resistant safety-shoes or boots. If skin contact is possible, wear inpenetrable protective clothing against this solvent.

SECTION 9: Physical and chemical properties

- General Information

- Appearance:

Form:
Colour:
Colourless
- Smell:
Odour threshold:
Alcohol-like
Not determined.

- pH-value:
- Melting point/freezing point:
- ~ -100 °C

- Melting point/freezing point: \sim -100 °C - Initial boiling point and boiling range: \geq 78 °C

- Flash point: ~13 ℃

- Inflammability (solid, gaseous) Not applicable.

- **Ignition temperature:** 425 °C Data for ethanol.

- Decomposition temperature: Not determined.

- **Self-inflammability:** Product is not selfigniting.

- **Explosive properties:** Product is not explosive. However, formation of explosive air/steam mixtures is possible.

- Critical values for explosion:

Lower: 3.5 Vol %
Upper: 15.0 Vol %
Data for ethanol.

- Vapour pressure at 20 °C: ~ 57 hPa

Density at 20 °C ~ 0.79 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

- Solubility in / Miscibility with

Water: Partly miscible

- Partition coefficient: n-octanol/water: Not determined.

- Viscosity:

dynamic:Not determined.kinematic:Not determined.

- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.

Printing date 21.01.2021 Version number 106 Revision: 05.01.2021

Trade name LPZ/II

(Contd. of page 5)

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

To avoid: warmth, flames, sparks

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials:

strong oxidizing agents

Aluminium, zinc and other light metals.

- 10.6 Hazardous decomposition products:

Formation of carbon monoxide and carbon dioxide in case of fire.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values that are relevant for classification:			
64-17-5 ethanol			
Oral	LD50	10,470 mg/kg (rat) (OECD 401)	
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)	
Inhalative	LC 50 / 4 h	>50 mg/l (rat) (OECD 403)	
		>20 mg/l (mouse)	

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Subacute to chronic toxicity: Can lead to liver dammage
- STOT-repeated exposure:

64-17-5 ethanol

Oral NOAEL 1,760 mg/kg (rat) (OECD 408, 90 d, target organ: liver)

- Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

no CMR effects available in according to present state of knowledge

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

64-17-5 ethanol

LC 50 / 48 h 8,140 mg/l (Leuciscus idus)

EC 50 / 48 h >10,000 mg/l (Daphnia magna)

(Contd. on page 7)

Printing date 21.01.2021 Version number 106 Revision: 05.01.2021

Trade name LPZ/II

(Contd. of page 6)

EC 50 / 72 h 275 mg/l (Chlorella vulgaris) (OECD 201)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- Respiratory inhibition of communal activated sludge EC 20 (mg/l according to ISO 8192 B):

64-17-5 ethanol

EC 50 (static) >100 mg/l (Chlorella pyrenoidosa) (OECD 201)

- Additional ecological information:
- General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods

The following advice is related to new material and not to any processed products. In case of a mixture with other products other disposal methods may become necessary. If in doubt seek advice from product supplier or from local authorities.

- Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. If possible, send to be recycled, otherwise burn or deposit in a certified facility.

- Waste disposal key number:

Since 01/01/99 the waste code numbers have not only been product-related but are also essentially application-related. The valid waste code number of the application can be obtained from the European waste catalogue.

- Uncleaned packagings: Disposal must be made according to official regulations.
- Recommendation:

Rented packaging: After optimal emptying, close immediately and return to the supplier without cleaning. Care should be taken that no other materials get into the packaging.

Other containers: After complete emptying and cleaning, send to be reconditioned or recycled.

Caution: Leftovers in the containers may cause the risk of explosion.

Uncleaned containers should not be perforated, cut or welded.

SECTION 14: Transport information

- 14.1 UN-Number - ADR, IMDG, IATA	UN1170
- 14.2 UN proper shipping name - ADR	1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
- IMDG	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
- IATA	ETHANOL SOLUTION

(Contd. on page 8)

Printing date 21.01.2021 Version number 106 Revision: 05.01.2021

Trade name LPZ/II

(Contd. of page 7)

	(Contd. of page 7
- 14.3 Transport hazard class(es)	
- ADR	
- Class	3 (F1) Flammable liquids.
- Label	3
- IMDG, IATA	
- Class	3 Flammable liquids.
- Label	3
- 14.4 Packing group	
- ADR, IMDG, IATA	II .
- 14.5 Environmental hazards:	Not applicable.
- Marine pollutant:	No
- 14.6 Special precautions for user	Warning: Flammable liquids.
- Kemler Number:	33
- EMS Number:	F-E,S-D
- Stowage Category	Α
- 14.7 Transport in bulk according to Ani	nex II of
Marpol and the IBC Code	Not applicable.
- Transport/Additional information:	
- ADR	
- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
- IMDG	
- Limited quantities (LQ)	1 <u>L</u>
- Excepted quantities (EQ)	Código E4
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN1170, ETHANOL SOLUTION (ETHYL ALCOHOL
	SOLUTION), 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Labelling according to Regulation (EC) No 1272/2008
 - The product is classified and labelled according to the CLP regulation.
- Hazard pictograms





GHS02 GHS07

- Signal word Danger
- Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Version number 106 Revision: 05.01.2021 Printing date 21.01.2021

Trade name LPZ/II

(Contd. of page 8)

- Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- National regulations
- Information about limitation of use:

Employment restrictions concerning young persons must be observed.

96% volatile organic compounds (Swiss Ordinance on the Incentive Tax on Volatile Organic Compounds).

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

UFI market placements:

Germany, Bulgaria, Denmark, Estonia, Finland, France, Greece, Ireland, Iceland, Latvia, Lithuania, Malta, Netherlands, Norway, Austria, Poland, Portugal, Sweden, Slovakia, Slovenia, Cyprus.

Relevant phrases

Complete wording of hazard statements and risk phrases (H- and R-phrases) mentioned in section 3. These phrases refer to the constituents. The labelling for this product is stated in section 2.

- Department issuing data specification sheet: see item 1: Informing department

Abbreviations and acronvms:

LEV. Local Exhaust Ventilation

NOAEL: No Observed Adverse Effect Level

RPE: Respiratory Protective Equipment

RCR: Risk Characterisation Ratio (RCR= PEC/PNEC)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Classification, Labelling and Packaging (Regulation (EC) No. 1272/2008)

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)

ISO: International Organisation for Standardisation

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

* Data compared to the previous version altered.